



Model: RHX-WM2

Wall Mount Relative Humidity Transmitter



FEATURES & BENEFITS

- Designed For Wall Mount Applications
- Accurate To +/- 3 % Relative Humidity
- Available with 0-1Vdc, 0-5Vdc or 4-20mA Output
- PVC Enclosure with Mounting Hardware

APPLICATIONS

- Laboratory and Research Facilities
- Storage Room, Wine Cellar
- Industrial Environmental Monitoring

DESCRIPTION

Model RHX-WM2 transmitter features fast response time, long-term stability, good accuracy and repeatable measurements. Designed for wall mounting, this model transmitter has an accuracy of +/- 3 % RH and provides an industry standard analog output of 0-5 Vdc, 0-1Vdc, or 4-20mA.

Specifications

Humidity Range:	0 – 100 % RH
Humidity Accuracy:	+/- 3 % RH (15 to 85 %) @23°C
Ambient Temperature:	-13 to 185 °F (-25 to 85 °C)
Wiring Connection:	Internal terminal block (16-24 AWG)
Enclosure:	Plastic, PVC



State-of-the-art Electronic Module

Available Models

Model Number	Output	Operating Voltage	Description
RHX-WM2-01	0 – 1V DC	7 to 24V DC	Wall Mount Humidity Transmitter, Voltage Output
RHX-WM2-05	0 – 5V DC	7 to 24V DC	Wall Mount Humidity Transmitter, Voltage Output
RHX-WM2-420	4 – 20 mA	8 to 12V DC	Wall Mount Humidity Transmitter, Current Output

© 2019 :: Imagine Instruments LLC :: 4500 Williams Drive, Ste 212-318 :: Georgetown, TX 78633 :: p. (855)574-6243
 e-mail: info@imagineinstruments.com :: www.imagineinstruments.com

Note: Continued product improvements make specifications subject to change without notice.
 Check www.imagineinstruments.com for the latest product information and updates
 Released: 18 February, 2019 :: Rev: A