



Activate Alarm with Any Dry-contact Switch!

DESCRIPTION

Universal Alarm Box

Series: UAB1-XL

FEATURES & BENEFITS

Compact, Industrial Design for Indoor Use
Audible Buzzer / Visual Red Strobe
External Power , Test and Silence Switch
Models For 12V DC, 24V DC or 120V AC Operation
Provides Latching Alarm Silence / Reset Function

APPLICATIONS

Sump Pump Basins, Holding Tanks
Water, Holding & Sewage Tanks
High or Low Temperature Warning
Industrial Process Monitoring
Use With Flow and Level Switches

Series UAB1-XL Universal Alarm Box is designed for indoor use. The unit features a non-metallic rugged enclosure, a combination red LED strobe/piezo buzzer, and external "power", "Test" and "Silence" switches. The unit is design to provide an audible and visual warning to notify of an alarm condition. Any dry-contact, non-powered flow, level, pressure or temperature switch will activate the alarm.

Specifications

Model No:	UAB1-XL-12VDC	UAB1-XL-24VDC	UAB1-XL-120VAC
Alarm Indication:	Intermittent Red LED Strobe/Piezo Horn: 85 dB		
Operating Voltage:	12V DC	24 VDC	120V AC, 50/60Hz
Alarm Silence:	Latching Function with Automatic Reset		
Switch Connection:	Internal Terminal Block		
Enclosure:	Wall Mounted (PVC) Plastic		
Operating Temperature:	-40 to 175 °F (-40 to 80 °C)		
Installation:	For Indoor Use Only (Unit is not weatherproof)		
Dimensions:	4 X 4 x 2" (102 x 102 x 51mm)		

© 2016 :: Imagine Instruments LLC :: 4500 Williams Drive, Ste 212-318 :: Georgetown, TX 78633 :: p. (855)574.6243 e-mail: info@imagineinstruments.com :: www.imagineinstruments.com

Note: Continued product improvements make specifications subject to change without notice. Check www.imagineinstruments.com for the latest product information and updates

Released: 31 March, 2016:: Rev: A