

# Model: UAP2-120VAC



Alarms are activated by any two dry-contact flow, level, temperature, or pressure switches!

# Dual Universal Alarm Panel

## FEATURES & BENEFITS

Rugged, Industrial Design for Indoor/Outdoor Use 88db Audible Piezo Horn Large Red/Amber Indicator Lights Power, Silence & Test Switch 120V AC, 50/60 Hz Operation Automatic Alarm Reset

#### APPLICATIONS

Sump Pump Basins, Holding Tanks Water, Holding & Sewage Tanks High or Low Temperature Alarm Industrial Process Monitoring Level, Flow or Pressure Alarm

Model UAP2-120VAC Universal Dual Alarm Box is designed for indoor or outdoor use. The unit features a nonmetallic, NEMA 4X, rugged enclosure, red and amber warning indicator lights, piezo horn, and an external "power", silence" and test switch. The unit is design to provide a loud audible and visual warning to notify of up to two alarm conditions. Any type pressure, flow, level or temperature switch will activate this alarm panel.

Model No:	UAP2-120VAC
Alarm Indication:	Red/Amber Indicator Lights, Piezo Horn: 88 dB
Operating Voltage:	120 VAC 50/60 Hz
Alarm Reset:	Automatic
Dual Switch Connection:	Terminal Blocks ( Dry Contact Input Only)
Enclosure:	Wall Mounted, (PC/PBT) Plastic, NEMA 4X
Power Connection:	Terminal Block
Operating temperature:	-40 to175 °F (-40 to 80 °C)
Installation:	For Indoor or Outdoor Use
Dimensions:	5.9 X 5.9 x 3.54" (150 x 150 x 90mm)

### Specifications

DESCRIPTION

© 2013 :: Imagine Instruments LLC :: 4500 Williams Drive, Ste 212-318 :: Georgetown, TX 78633 :: p. 855.574.6243 e-mail: info@imagineinstruments.com :: www.imagineinstruments.com

Note: Continued product improvements make specifications subject to change without notice. Check www.imagineinstruments.com for the latest product information and updates

Released: 21 April, 2013 :: Rev: B